



DECLARATION OF PERFORMANCE

No. FLORIM 001

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5$ %

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

FLORIM CERAMICHE S.p.A.,

Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory, if relevant – **Not applicable**

Task(s) carried out

AVCP system

Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	Based on the decision 96/603/CE and its changes EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 25/06/2013

.....
Place and date of issue

.....
Signature



FLORIM CERAMICHE S.p.A. a socio unico

VIA CANALETTO 24 / 41042 FIORANO MODENESE MO ITALY / T. +39 0536 840111 / F. +39 0536 844750
WWW.FLORIM.IT / INFO@FLORIM.IT / CAPITALE SOCIALE EURO 50.000.000 I.V.

ISCR. AL REG. DELLE IMPRESE DELLA C.C.I.A.A. DI MODENA / COD. FISC. E P. IVA IT 01265320364

Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata

No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)

Rev. 2 del/of/de/vom/de/a 27/06/2014

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka


REX

Serie / Series / Kolekcja	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA D.M. 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ABISKO	α da 6° a 10°	> 0,4	R9	N.P.D.
ALABASTRI DI REX	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ARDOISE naturale	α da 11° a 19°	> 0,4	R10	N.P.D.
ARDOISE grip	α da 20° a 27°	> 0,4	R11	Classe 2
CHATEAUX DE LA LOIRE	α da 11° a 19°	> 0,4	R10	N.P.D.
CONCREATE	N.P.D.	N.P.D.	N.P.D.	N.P.D.
CREMA MARFIL SELECT naturale	α da 6° a 10°	N.P.D.	R9	N.P.D.
CREMA MARFIL SELECT lucido	N.P.D.	> 0,4	N.P.D.	N.P.D.
FRAMES	N.P.D.	> 0,4	R9	N.P.D.
I GIOIELLI DI REX (pavimento)	N.P.D.	N.P.D.	N.P.D.	N.P.D.
HORN	α da 6° a 10°	N.P.D.	R9	N.P.D.
GALUCHAT	N.P.D.	N.P.D.	R9	N.P.D.
GLAMWOOD	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I BIANCHI DI REX naturale	α da 6° a 10°	> 0,4	R9	N.P.D.
I BIANCHI DI REX lucido	N.P.D.	> 0,4	N.P.D.	N.P.D.
I MARMI DI REX lucido	N.P.D.	> 0,4	N.P.D.	N.P.D.
I MARMI DI REX naturale	α da 6° a 10°	> 0,4	R9	N.P.D.
LA ROCHE grip	α da 20° a 27°	> 0,4	R11	Classe 2
LA ROCHE smooth	α da 6° a 10°	> 0,4	R9	N.P.D.
LA ROCHE naturale	α da 11° a 19°	> 0,4	R10	Classe 1
LEAVES	α da 6° a 10°	> 0,4	R9	N.P.D.
LE CASCINE	N.P.D.	> 0,4	N.P.D.	N.P.D.
LE ESSENZE DI REX	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LE ESSENZE DI REX lucido	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LOGICA	N.P.D.	> 0,4	N.P.D.	N.P.D.
LOGICA GRAFFIATO	α da 20° a 27°	> 0,4	R11	N.P.D.

MAGISTRA ASPER	α da 11° a 19°	> 0,4	R10	N.P.D.
MAGISTRA PICTUM	N.P.D.	> 0,4	N.P.D.	N.P.D.
MATERRE	N.P.D.	> 0,4	R9	N.P.D.
MATOUCHE	N.P.D.	> 0,4	N.P.D.	N.P.D.
MATOUCHE – Croco	N.P.D.	N.P.D.	N.P.D.	N.P.D.
METAUX	N.P.D.	> 0,4	R9	N.P.D.
METROWALL	N.P.D.	N.P.D.	N.P.D.	N.P.D.
PIERRES NATURALE	α da 6° a 10°	> 0,4	R9	N.P.D.
PIERRES LUCIDA	α da 6° a 10°	N.P.D.	R9	N.P.D.
PIERRES STRUTTURATO	α da 20° a 27°	> 0,4	R11	N.P.D.
PIETRA DEL NORD SOFT	N.P.D.	> 0,4	N.P.D.	N.P.D.
PIETRA DEL NORD ANTICATO	α da 11° a 19°	> 0,4	R10	N.P.D.
PIETRA DEL NORD STRUTTURATO	α da 20° a 27°	> 0,4	R11	Classe 2
PILLARGURI	N.P.D.	> 0,4	R9	N.P.D.
ROSA DEL DESERTO	α da 11° a 19°	> 0,4	R10	N.P.D.
SELECTION OAK	α da 6° a 10°	> 0,4	R9	N.P.D.
SELECTION OAK STRUTTURATO	α da 20° a 27°	> 0,4	R11	N.P.D.
SHABUI	N.P.D.	> 0,4	R10	N.P.D.
SLATE SOLUTIONS	N.P.D.	> 0,4	R9	N.P.D.
STRIPES	N.P.D.	N.P.D.	R9	N.P.D.
TAIGA	α da 6° a 10°	N.P.D.	R 9	N.P.D.
TAIGA GRIP	α da 20° a 27°	> 0,4	R11	N.P.D.
TOUCH STONE	N.P.D.	N.P.D.	N.P.D.	N.P.D.
UNIQUE grip	α da 20° a 27°	> 0,4	R11	N.P.D.
UNIQUE naturale	α da 6° a 10°	> 0,4	R 9	N.P.D.

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass